

CONTENTS AND ABSTRACTS

DATA TRANSMISSION AND PROCESSING

V.I. Koshelev, V.A. Belokurov. USAGE OF INTERACTING MULTIPLE MODEL KALMAN FILTER IN ATTITUDE HEADING REFERENCE SYSTEM OF HIGH MANEUVERING OBJECT

Key words: interacting multiple model Kalman filter, yaw, roll, pitch.

Possibility of multiple model Kalman filter application in attitude heading reference system of high maneuvering object allowing to increase precision of an estimation yaw, roll, pitch at maneuvers with high accelerations is shown.....3

V.K. Klochko. SUPERVISION SYSTEMS RESOLUTION INCREASE WITH THE PHASED ANTENNA BAR BY METHOD OF IMAGE RESTORATION

Key words: resolution, phased antenna bar, radar-location, radio-thermal location.

The possibility of resolution increase of both radio and thermal-location supervision systems with the phased antenna bar by means of additional algorithmic processing of reflected or radiated signal by method of restoration of reflection or radiation field is investigated. The results of modeling are given.....7

V.G. Andreev. AUTOREGRESSIVE MODELS OF RADIO REFLECTIONS OPTIMIZATION

Key words: linear autoregression, spectrum, time sequences modeling, redefined Yule-Walker's equation.

The method for linear autoregressive models of radio reflections optimization, based on the procedure of autoregression coefficients vector weighing by a correction multiplier is offered and investigated. It is shown that the offered method allows to reduce 2...4 times computing expenses needed for redefined autoregressive model of radio reflections. The result is reached thanks to an exception of rectangular correlation matrixes of modeled process multiplication in redefined system of the linear equations solution.....12

A.Y. Linovich. AN EQUALIZER WITH THE ADAPTIVE STRUCTURE OF THE ANALYSIS/SYNTHESIS SYSTEM

Key words: multirate signal processing, dynamic structure.

The structure and the adaptive algorithm of the complex subband equalizer are submitted. The simulation results which confirm the series of advantages of the subband equalizer with the adaptive analysis/synthesis system over conventional equalizers are presented15

I.A. Saitov, N.I. Myasin, R.B. Tregubov, A.V. Knysh. PROJECTING OF DISTRIBUTED SUBSCRIBER CONCENTRATOR OF MULTISERVICE NETWORK

Key words: next generation network, softswitch, package commutation, IP-telephony, access gateway, transfer technology.

Some problems of next generation networks creation in Russia are considered in the article. The parameters calculation of next generation network part based on distributed subscriber concentrator is suggested22

RADIOTECHNICAL AND MEASURING SYSTEMS

S.N. Kirillov, P.S. Pokrovsky. PERMANENT PREDICTION ALGORITHM FOR MOTION TRAJECTORY OF SPACE OBJECT BASED ON MODIFIED GROUP METHOD OF DATA HANDLING

Key words: method of a group data handling, long-term forecasting, space object, combination performance criterion.

The new prediction algorithm for motion trajectory of space object was offered. The algorithm utilizes nonphysical prediction models obtained from modified group method of data handling. With the help of simulation it was shown that introduced algorithm application allows to reduce influence of entry condition errors. Prediction error reduce as compared with classical prediction algorithm in the range between 1,5...100 was proved. The given modification ensures additional 20...25 % increase of forecast precision31

I.V. Baranov, V.V. Ezersky. TAKING INTO ACCOUNT NONLINEAR MODULATION CHARACTERISTICS OF THE TRANSMITTER WHEN AVERAGED DIFFERENCE WEIGHTED FREQUENCY IN THE FREQUENCY RANGE FINDERS OF INDUSTRIAL APPLICATIONS

Key words: short-range radar, frequency modulation, the error of distance measurement, modulation characteristics nonlinearity influence, effect of nonlinearity.

The influence of modulation characteristics nonlinearity of the transmitter on the accuracy of distance measurements is investigated, characteristic features depending on the distance measurement error for different types of nonlinearity are identified, the method of nonlinearities effect during distance calculation based on nonlinearity parameters obtained from difference frequency working signal is proposed.....35

V.F. Odinokov. THE FREQUENCY-PHASE CIRCUIT FOR CARRIER RECOVERY

Key words: frequency-phase circuit, frequency detector.

The strategy for frequency-phase self-tuning and the structure of frequency detector of carrier recovery system are offered.....42

O.K. Abramov, A.Y. Klochkov, P.V. Safonov. THE ERRORS OF DIGITAL MEASURING INSTRUMENTS AND INTELLIGENT MEASURING SYSTEMS IN THE PRESENCE OF NOISE AND INTERFERENCE

Key words: measuring instruments, measuring systems, random processes, errors.

Errors sources systematisation of digital measuring instruments (MI) and virtual equipment in the presence of noise is given. Mathematical and statistical models of errors estimation are considered and methods of machine implementation of random processes probable characteristics are suggested.....47

A.N. Bystrov, V.I. Djigan. INFLUENCE OF RADAR SIGNAL SAMPLING ON THE CHARACTERISTICS OF DETECTORS

Key words: digital signal detector, detection performance, sampling, stroboscopic sampling.

The influence of input signal sampling on the detection performance of digital detectors is considered. The detection performance is calculated taking into account signal sampling. A comparative analysis of stroboscopic and conventional sampling showed that in the case of high signal-to-noise ratio it is expedient to use stroboscopic sampling.....55

COMPUTER SCIENCE AND APPLIED MATHEMATICS

V.V. Belov, A.N. Myskin. THE CONCEPT OF INTELLIGENT SYSTEM FOR THE ANALYSIS OF SOFTWARE PROJECTS STATE

Key words: ontology, forecasting, project management, metrics.

A concept of the information system designed to analyze the state of software projects, identify risks, determine optimal corrective measures on the basis of forecasts of controlled processes (metrics) is proposed. An ontological model of forecasting methods, project metrics, risks, project management methodologies and experience in their application in practice for the unification of approach to the collection and presentation of knowledge in the field of

information technology is developed. The usefulness of the proposed system for projects managing in modern IT companies is evaluated.....59

A.P. Martynov. SAFE OPERATION MAINTENANCE OF SOFT HARDWARE IN THE COURSE OF THEIR INITIALIZATION

Key words: loader, system configuration, data transformation, operating system.

Variants of structural software loaders construction are presented, on their basis the universal loader is offered and practical recommendations about its use for reliable functioning of soft hardware are given.....66

A.I. Baranchikov, S.E. Kukharev. METHODS OF ATTRIBUTES PRIVACY REENGINEERING IN RELATIONAL DATABASES

Key words: reengineering, databases, relational, design, information system, privacy, access, a mandatory method, a discretionary method.

Algorithms of attributes privacy reengineering in the information system with mandatory and discretionary access methods are considered in the article. The estimation of time complexity of algorithm is made72

G.S. Orlov. MEASURABLE SPACE OF LOCALIZATION OF COMMON DYNAMIC PROBABLE LOADED GRAPH TOPS, ADMITTING SPLITTING INTO TOPS RESPONSIBILITY ZONES

Key words: generalized dynamic probable loaded graph, measurable space, measure, integral on a measure.

Based on the concept of generalized dynamic probable loaded graph entered earlier by the author, measurable space of localization area of its tops for the case when this area supposes splitting into graph tops responsibility zones is developed. The function of sets is defined, the measure is set, appropriate integral on a measure is entered, its basic properties are analyzed75

D.V. Gurov, M.A. Ivanov. DYNAMIC RANDOMIZATION OF MICROPROCESSOR COMMAND SYSTEM FOR EXPLOIT SAFEGUARD

Key words: microprocessor architecture, command system, software vulnerabilities, security, LFSR, randomization.

This paper deals with protection methods of programs containing vulnerabilities by means of pointed changes of microprocessor architecture. Modifications of IA-32 architecture have been taken as an example. These modifications concern the hardware-based encryption of command system. This encryption is unique for each process under execution in the system. Efficiency of this modification in relation to security and performance has been shown.....81

D.Yu. Muzalevsky, S.I. Saitov. MODEL OF A FIBER-OPTIC LINEAR TRACT WITH DENSE WAVELENGTH DIVISION MULTIPLEXING SYSTEMS AND A FIBER-OPTIC AMPLIFIER AS A CONTINUOUS CONTROL OBJECT

Key words: model of the fiber-optic linear tract, intensity of the optical signal, controlled parameters, methodical validity of the control, continuous control.

A new information-measuring model of a heterogeneous fiber-optic linear tract of dense wavelength division multiplexing systems and a fiber-optic amplifier as a continuous control object in the monitoring system of multiprotocol transport telecommunications net of a new generation is offered86

ELECTRONICS

S.M. Karabanov, D.V. Suvorov, B.N. Sazhin, E.V. Slivkin. CLEARING OF SILICON BY EXTRACTION METHOD FROM A FIRM PHASE

Key words: mathematical modeling, silicon clearing, solar quality silicon reception, impurities diffusion.

The aim of the work is to elaborate an improved mathematical model of silicon clearing process by extraction method from a firm phase, to calculate different impurities diffusion modes, to evaluate quantitatively basic parameters of a technological process when high clearing effectiveness is achieved. The diffusion of basic impurities determining the quality of solar silicon, i.e. boron, phosphorus, aluminium, carbon, iron and copper, has been considered. The results of impurity concentration distribution on particles section in various moments of time, the dynamics of average concentration change of each impurity in time under various conditions - temperature, diameter of particles, various silicon and substance-extragent volumes parities - are presented. The obtained data give the possibility to use the presented technology for industrial silicon clearing for the purpose of silicon reception for solar power93

N.M. Vereschagin, S.A. Kruglov, A.A. Serezhin, A.I. Maisuradze. DISTRIBUTION OF ENERGY ON STAGE OFF DISCHARGE BREAKER INCLUDED IN THE PLAN INDUCTIVE ENERGY STORAGE

Key words: inductive energy storage, discharge breaker, energy losses in a switch.

Energy characteristics of a discharge current interrupter included in the scheme of the inductive storage energy are considered. Approximating functions of anode current and the voltage on the anode at the time of commutation for three voltage ranges are received. The biggest energy losses in the switch are proved to appear in the third voltage range98

MANAGEMENT

A.P. Kazantsev. VECTOR OPTIMIZATION OF AUTOMATED SYSTEMS

Key words: automated systems, optimization, Pareto set, quality indicator, accumulation rate of profit.

The justification of double stage approach to system optimization is explained. The method to detect effective vectors with Pareto set approximation is suggested. The scalar value of Productivity to Production Cost ratio is proved to be an adequate quality indicator. The graphical/numerical decision making method for the set of Pareto alternatives based upon accumulation rate of profit criterion is offered103

E.L. Eremin, D.A. Telichenko, E.A. Shelenok. PERIODIC MODES IN DECENTRALIZED ADAPTIVE AND ROBUST CONTROL CIRCUITS

Key words: multiloop plant, priority uncertainty, hyper stability criterion, stationary observer, over-and-inertial reference model.

The article considers adaptive and robust decentralized repetitive control for nonlinear priority uncertain multiloop plants. System synthesis based on hyper stability criterion, quick-response reference model and applepie order stationary observer is given108

BRIEF REPORTS

A.V. Brykov, B.I. Kolotilin. THE ANALYSIS OF INFLUENCE FRONTS OF RF SIGNAL PULSES ON STABILITY DIAGRAM AND ON RESOLUTION OF THE 3D ION TRAP

Key words: axially symmetric ion trap, resolution, pulse rf signal, the pulse rf signal "EC-signal".

The analysis of influence of fronts duration change of pulses rf signal "EC-signal" used for power supply of electrodes of the axially symmetric ion trap on a pattern of a combined stability diagram and the resolution is carried out. On the basis of numerical modeling results the parameters of period pulse rf signal allowing to diminish of influence fronts of pulses are defined117

S.N. Buzykanov. THE SCANNED TEXT RESTORATION ALGORITHM IN WEIGHTED SOBOLEV SPACE

Key words: low-frequency function filtering, weight Sobolev space W_2^1 , digital image processing.

An algorithm of images low-frequency filtration in the weight Sobolev space W_2^1 is proved. The application of a given algorithm is offered to process an image scanned with poor resolution in the weight Sobolev space W_2^1 which allows to improve the quality and legibility of the text by 4 points on a ten-mark scale. A criterion of α weight factor selection to create automated scanning results processing systems is proved 120

R.V. Ivanenko, L.V. Vorobjev, R.R. Ivanenko. SPEECH TRANSMISSION IMPROVEMENT OF QUALITY IN NETWORKS WITH PACKAGE SWITCHING

Key words: management algorithm, buffer store, transmission quality, package switching, throughput, imitation modelling, storage budgets, commutation node.

The algorithm of buffer store memory size management which provides optimal node throughput (minimum possible size of blocking) is received at the given loading, volume of the store and throughputs of proceeding lines, and also the demanded size of a packages delay in a node. The application of developed algorithm increases throughput by 30 % in comparison with switching of channels, and by 12 % – in comparison with packages switching..... 123

I.A. Nemchenko, D.B. Nikolaev. QUALITATIVE INFORMATION COMPONENT PROTECTION WITH USE OF STOCHASTIC ALGORITHMS

Key words: integrity, qualitative characteristic, mathematical model, stochastic transformation.

The analysis of the qualitative information component in aspect of its value for the malefactor is carried out. On the basis of the carried out analysis the mechanisms of safety and data integrity based on stochastic transformation usage are offered..... 126

In commemoration of Yuri Mikhailovich Korshunov 129

INFORMATION ABOUT THE AUTHORS (Russian) 130

INFORMATION ABOUT THE AUTHORS (English)..... 132